

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Issue date: 16-4-2020 Revision date: 13-10-2020 Supersedes: 10-6-2020 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	
Product name	
Product code	
Product group	

: Mixture : ENEOS ATF DSG : V161500445 : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public Main use category Use of the substance/mixture Function or use category

: industrial use, professional use, consumer use

: Lubricant

: Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

ENEOS Europe Limited 2F Bury House, 31 Bury Street, London, EC3A 5AR United Kingdom

1.4. Emergency telephone number

Emergency number

: 0044 20 7186 0400 (Monday to Friday: 8:00 - 17:00)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272	2/2008 [CLP]
Precautionary statements (CLP) EUH-statements Child-resistant fastening Tactile warning	 P102 - Keep out of reach of children. EUH210 - Safety data sheet available on request. Not applicable Not applicable
2.3. Other hazards	
Other hazards not contributing to the classification	: This product floats on water and may affect the oxygen-balance in the water. The base oil

contains less than 3% DMSO-extract measured according IP 346, therefore it is NOT classified as T/R45: May cause cancer" (Note L).".

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Lubricating oils (petroleum), C20-C50, hydrotreated neutral oil-based	(CAS-No.) 72623-87-1 (EC-No.) 276-738-4 (REACH-no) 01-2119474889-13	≥ 50	Asp. Tox. 1, H304
Methacrylate copolymer	(CAS-No.) confidential	3 – 5	Eye Irrit. 2, H319
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.]	(CAS-No.) 64742-54-7 (EC-No.) 265-157-1 (EC Index-No.) 649-467-00-8 (REACH-no) 01-2119484627-25	3 – 5	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated light paraffinic	(CAS-No.) 64742-55-8 (EC-No.) 265-158-7 (EC Index-No.) 649-468-00-3 (REACH-no) 01-2119487077-29	1 – 3	Asp. Tox. 1, H304
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil - unspecified	(CAS-No.) 72623-86-0 (EC-No.) 276-737-9 (REACH-no) 01-2119474878-16	1 – 3	Asp. Tox. 1, H304

Full text of H-statements: see section 16

SECTION 4: First aid measures

: Seek medical attention if ill effect develops.
Take victim to fresh air, in a quiet place, in an half laying position and if necessary take medical advice. Allow the victim to rest.
: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. High-pressure injection under skin may cause serious damage. Seek medical attention if ill effect or irritation develops.
: Remove contact lenses, if present and easy to do. Continue rinsing. Ensure adequate flushing of eyes by separating eyelids with the fingers. Obtain medical attention if pain, blinking, tears or redness persist.
: Consult a doctor/medical service if you feel unwell. If vomiting occurs spontaneously, keep head below the hips to prevent aspiration. Do not induce vomiting.
ects, both acute and delayed
At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.
: At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or
 At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs. Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis. High pressure injection of product into the skin may lead to

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Symptoms/effects upon intravenous administration : Unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures	5
5.1. Extinguishing media	
Suitable extinguishing media Unsuitable extinguishing media	 carbon dioxide (CO2), dry chemical powder, foam. Water fog. Do not use a heavy water stream. Use of heavy stream of water may spread fire.
5.2. Special hazards arising from the	substance or mixture
Fire hazard Explosion hazard	 Combustion generates: CO, CO2, POx, NOx, SOx, H2S. Not expected to be a fire/explosion hazard under normal conditions of use.
5.3. Advice for firefighters	
Precautionary measures fire Firefighting instructions Protection during firefighting Other information	 Do not enter fire area without proper protective equipment, including respiratory protection. Use water spray or fog for cooling exposed containers. Use self-contained breathing apparatus and chemically protective clothing. Prevent fire fighting water from entering the environment. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations.

SECTION 6: Accidental release meas	sures
6.1. Personal precautions, protective equ	uipment and emergency procedures
General measures	: Spill area may be slippery. Prevent soil and water pollution. Prevent entry to sewers and public waters.
6.1.1. For non-emergency personnel	
Protective equipment	: When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required. Use protective clothing.
Emergency procedures	: Consider evacuation.
6.1.2. For emergency responders	
Protective equipment	: When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.
Emergency procedures	: No specific measures are necessary.
6.2. Environmental precautions	

Dike for recovery or absorb with appropriate material. Notify authorities if product enters sewers or public waters. Prevent soil and water pollution. Prevent liquid from entering sewers, watercourses, underground or low areas. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

6.3. Methods and material for cont	ainment and cleaning up
For containment	: Large quantities: Contain large spillage with sand or earth.
Methods for cleaning up	: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Take up large spills with pump or vacuum and finish with dry chemical absorbent.
Other information	: Use suitable disposal containers. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations. On water, recover/skim from surface and pour out in disposal container.

6.4. Reference to other sections

For further information refer to section 13.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 7: Handling and storage 7.1. Precautions for safe handling Additional hazards when processed : Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. Precautions for safe handling Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or smoke during use. Remove contaminated clothing and shoes. Hygiene measures : Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep container tightly closed and in well ventilated place.
Storage conditions	: Keep only in original container.
Incompatible products	: Reacts vigorously with strong oxidizers and acids.
Maximum storage period	: 5 year
Storage temperature	: ≤40 °C
Information on mixed storage	: Keep away from : oxidizing materials. Strong acids.
Storage area	: Store at ambient temperature.
Special rules on packaging	: Keep container tightly closed and dry.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure-value for oil mist

: 10 mg/m3 (15 min.) or 5 mg/m3 (8 hours).

8.2. Exposure controls

Appropriate engineering controls:

Large quantities: Contain large spillage with sand or earth.

Personal protective equipment:

Gloves. In case of splash hazard: safety glasses. Eye protection should only be necessary where liquid could be splashed or sprayed.

Materials for protective clothing:	
PVC gloves. Neoprene or nitrile rubber gloves	
Hand protection:	

In case of repeated or prolonged contact wear gloves. The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream). The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

Eye protection:

Eye protection should only be necessary where liquid could be splashed or sprayed

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use. Avoid repeated or prolonged skin contact. If repeated skin contact or contamination of clothing is likely, protective clothing should be worn. Equipment should conform to EN 166.

Respiratory protection:

Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure. Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment. Respiratory protective equipment must be checked to ensure it fits correctly each time it is worn. Provided an air-filtering/air-purifying respirator is suitable, a filter for particulates can be used for mist or fume. Use filter type P or comparable standard. A combination filter for particles and organic gases and vapours (boiling point >65°C) may be required if vapour or abnormal odour is also present due to high product temperature. Use filter type AP or comparable standard.

Personal protective equipment symbol(s):



Environmental exposure controls: See Heading 12. See Heading 6.

Consumer exposure controls:

PVC gloves. Neoprene or nitrile rubber gloves.

Other information:

Do not put the product-soaked rags into the pockets of working clothes. Do not use cloths stained with the product to dry hands. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke during use. Wash contaminated clothing before reuse.

9.1. Information on basic physical and chemical properties

Physical state	: liquid
Appearance	: Oily. liquid.
Colour	: amber.
Odour	: characteristic.
Odour threshold	: No data available
рН	: No data available
Relative evaporation rate (butylacetate=1)	: < 0,1
Melting point	: -45 °C
Freezing point	: No data available
Boiling point	: > 280 °C
Flash point	: 143 °C
Auto-ignition temperature	: > 240 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour Pressure 20°C	: < 0,1 hPa
Relative vapour density at 20 °C	: > 1 (air=1)
Relative density	: No data available
Density	: 0,84 – 0,85 kg/l
Solubility	: insoluble in water.
Log Pow	: > 3
Viscosity, kinematic	: 25 – 50 mm²/s
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 0,6 – 7 vol %
9.2. Other information	

VOC content Other properties : 0%

: Gas/vapour heavier than air at 20'C.

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

according to Regulation (EC) No. 1907/2006 (REACH)	
SECTION 10: Stability and reactivity	
10.1. Reactivity	
Stable under normal conditions of use.	
10.2. Chemical stability	
Stable under normal conditions.	
10.3. Possibility of hazardous reactions	
Refer to section 10.1 on Reactivity.	
10.4. Conditions to avoid	
Moisture. Overheating.	
10.5. Incompatible materials	
Strong oxidizing agents. Strong acids.	
10.6. Hazardous decomposition produc	ts
No additional information available	
SECTION 11: Toxicological informa	tion
11.1. Information on toxicological effect	ts
Acute toxicity (oral)	: Not classified
Acute toxicity (dermal) Acute toxicity (inhalation)	: Not classified : Not classified
obtained by treating a petroleum fraction carbon numbers predominantly in the r (19cSt at 40°C). It contains a relatively I	eavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons on with hydrogen in the presence of a catalyst. It consists of hydrocarbons having range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F large proportion of saturated hydrocarbons.] (64742-54-7)
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 5000 mg/kg
LC50 Inhalation - Rat	> 5,53 mg/l
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation Respiratory or skin sensitisation	: Not classified : Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
ENEOS ATF DSG	
Viscosity, kinematic	25 – 50 mm²/s
Other information	: Toxicological data have not been determined specifically for this product. Information give

route of exposure: ingestion, skin and eye.

is based on a knowledge of the components and the toxicology of similar products. Likely

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general Ecology - water Hazardous to the aquatic environment, short-term facute) Hazardous to the aquatic environment, long-term ichronic)	 Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. This product floats on water and may affect the oxygen-balance in the water. Not classified Not classified
obtained by treating a petroleum fraction wi carbon numbers predominantly in the range	paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons th hydrogen in the presence of a catalyst. It consists of hydrocarbons having of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F proportion of saturated hydrocarbons.] (64742-54-7)
LC50 fish 1	100 mg/l
EC50 Daphnia 1	10000 mg/l
Lubricating oils (petroleum), C15-30, hydrot	reated neutral oil-based; Baseoil - unspecified (72623-86-0)
NOEC chronic algae	≥ 100 mg/l 72h
12.2. Persistence and degradability	
ENEOS ATF DSG	
Persistence and degradability	Not readily biodegradable.
obtained by treating a petroleum fraction wi carbon numbers predominantly in the range	paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons ith hydrogen in the presence of a catalyst. It consists of hydrocarbons having of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F proportion of saturated hydrocarbons.] (64742-54-7)
Biodegradation	31 %
12.3. Bioaccumulative potential	
ENEOS ATF DSG	
ENEOS ATF DSG Log Pow	> 3
	> 3This product is not expected to bioaccumulate through food chains in the environment.
Log Pow	
Log Pow Bioaccumulative potential	
Log Pow Bioaccumulative potential 12.4. Mobility in soil	
Log Pow Bioaccumulative potential 12.4. Mobility in soil ENEOS ATF DSG	Not miscible with water. Spillages may penetrate the soil causing ground water contamination. This product floats on water and may affect the oxygen-balance in the
Log Pow Bioaccumulative potential 12.4. Mobility in soil ENEOS ATF DSG Ecology - soil	Not miscible with water. Spillages may penetrate the soil causing ground water contamination. This product floats on water and may affect the oxygen-balance in the
Log Pow Bioaccumulative potential 12.4. Mobility in soil ENEOS ATF DSG Ecology - soil 12.5. Results of PBT and vPvB assessment	Not miscible with water. Spillages may penetrate the soil causing ground water contamination. This product floats on water and may affect the oxygen-balance in the

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 13: Disposal considerations

13.1. Waste treatment methods Regional legislation (waste) : Disposal must be done according to official regulations. Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not discharge into drains or the environment. Additional information Hazardous waste. : Ecology - waste materials Every mixture with foreign substances such as solvents, brake- and cooling liquids is forbidden. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. When not empty dispose of this container at hazardous or special waste collection point. 13 02 06* - Synthetic engine, gear and lubricating oils

European List of Waste (LoW) code

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	ΙΑΤΑ	ADN	RID	
14.1. UN number					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.2. UN proper shippin	g name	· · · · · ·			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.3. Transport hazard o	class(es)	· · · · · ·			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.4. Packing group		· · · · ·			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.5. Environmental haz	zards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
No supplementary informatic	on available	· ·		·	

14.6. Special precautions for user

Overland transport Not applicable Transport by sea Not applicable Air transport Not applicable Inland waterway transport Not applicable Rail transport Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 0 %

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:	
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
EUH210	Safety data sheet available on request.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.