

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Issue date: 8-8-2016 Revision date: 13-10-2020 Supersedes: 8-8-2016 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	
Product name	
Product code	
Product group	

Mixture
 ENEOS GP4T Performance Racing 5W-30
 V161500414
 Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public Main use category Use of the substance/mixture Function or use category

: industrial use, professional use, consumer use

: Lubricant

: Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

ENEOS Europe Limited 2F Bury House, 31 Bury Street, London, EC3A 5AR United Kingdom

1.4. Emergency telephone number

Emergency number

: 0044 20 7186 0400 (Monday to Friday: 8:00 - 17:00)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]		
Precautionary statements (CLP) Child-resistant fastening Tactile warning	 P102 - Keep out of reach of children. Not applicable Not applicable 	
2.3. Other hazards		
Other hazards not contributing to the classification	: This product floats on water and may affect the oxygen-balance in the water. The base oil contains less than 3% DMSO-extract measured according IP 346, therefore it is NOT classified as T/R45: May cause cancer" (Note L).". USED ENGINE OILS: Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of	

maintained.

used engine oil must therefore be avoided and a high standard of personal hygiene

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Lubricating oils (petroleum), C20-C50, hydrotreated neutral oil-based	(CAS-No.) 72623-87-1 (EC-No.) 276-738-4 (REACH-no) 01-2119474889-13	≥ 50	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.]	(CAS-No.) 64742-54-7 (EC-No.) 265-157-1 (EC Index-No.) 649-467-00-8 (REACH-no) 01-2119484627-25	25 – 35	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated light paraffinic	(CAS-No.) 64742-55-8 (EC-No.) 265-158-7 (EC Index-No.) 649-468-00-3 (REACH-no) 01-2119487077-29	3 – 5	Asp. Tox. 1, H304
White mineral oil (petroleum)	(CAS-No.) 8042-47-5 (EC-No.) 232-455-8 (REACH-no) 01-2119487078-27	3 – 5	Asp. Tox. 1, H304
Phosphorodithioic acid, mixed O,O-bis (1,3- dimethylbutyl and iso-Pr)esters, zinc salts	(CAS-No.) 84605-29-8 (EC-No.) 283-392-8 (REACH-no) 01-2119493626-26	1 – 3	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411

Full text of H-statements: see section 16

SECTION 4: First aid measures

First-aid measures general : Seek medical attention if ill effect develops. First-aid measures after inhalation : Take victim to fresh air, in a quiet place, in an half laying pormedical advice. Allow the victim to rest. First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area of followed by warm water rinse. High-pressure injection under damage. Seek medical attention if ill effect or irritation develops. First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continuum flushing of eyes by separating eyelids with the fingers. Obtains blinking, tears or redness persist. First-aid measures after ingestion : Consult a doctor/medical service if you feel unwell. If vomith head below the hips to prevent aspiration. Do not induce volume the secure of its low volatility. May be harmful by inhalation if fumes resulting from thermal decomposition products occur.	with mild soap and water, er skin may cause serious elops. e rinsing. Ensure adequate
First-aid measures after eye contact First-aid measures after eye contact Remove contact lenses, if present and easy to do. Continue flushing of eyes by separating eyelids with the fingers. Obta blinking, tears or redness persist. First-aid measures after ingestion Consult a doctor/medical service if you feel unwell. If vomit head below the hips to prevent aspiration. Do not induce voltable because of its low volatility. May be harmful by inhalation if	er skin may cause serious elops. e rinsing. Ensure adequate
First-aid measures after ingestion flushing of eyes by separating eyelids with the fingers. Obtablinking, tears or redness persist. First-aid measures after ingestion Consult a doctor/medical service if you feel unwell. If vomiti head below the hips to prevent aspiration. Do not induce voltable with the hips to prevent aspiration. Do not induce voltable with the fingers. Obtable with the hips to prevent aspiration. Do not induce voltable with the hips to prevent aspiration. Do not induce voltable with the hips to prevent aspiration. Do not induce voltable. Symptoms/effects after inhalation At normal ambient temperatures this product will be unlikely because of its low volatility. May be harmful by inhalation if	•
4.2. Most important symptoms and effects, both acute and delayed Symptoms/effects after inhalation : At normal ambient temperatures this product will be unlikely because of its low volatility. May be harmful by inhalation if	· · · · · · · · · · · · · · · · · · ·
Symptoms/effects after inhalation : At normal ambient temperatures this product will be unlikely because of its low volatility. May be harmful by inhalation if	• • • •
because of its low volatility. May be harmful by inhalation if	
	exposure to vapour, mists or
Symptoms/effects after skin contact : Unlikely to cause harm to the skin on brief or occasional co exposure may lead to dermatitis. High pressure injection of local necrosis if the product is not surgically removed.	
Symptoms/effects after eye contact : Unlikely to cause more than transient stinging or redness if	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Symptoms/effects after ingestion

: Bad taste. Unlikely to cause harm if accidentally swallowed in small doses, though larger quantities may cause nausea and diarrhoea.

Symptoms/effects upon intravenous administration : Unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures			
5.1. Extinguishing media			
Suitable extinguishing media Unsuitable extinguishing media	carbon dioxide (CO2), dry chemical powder, foam. Water fog.Do not use a heavy water stream. Use of heavy stream of water may spread fire.		
5.2. Special hazards arising from the substance or mixture			
Fire hazard Explosion hazard	 Combustion generates: CO, CO2, POx, NOx, SOx, H2S. Metallic oxides. Not expected to be a fire/explosion hazard under normal conditions of use. 		
5.3. Advice for firefighters			
Precautionary measures fire Firefighting instructions Protection during firefighting Other information	 Do not enter fire area without proper protective equipment, including respiratory protection. Use water spray or fog for cooling exposed containers. Use self-contained breathing apparatus and chemically protective clothing. Prevent fire fighting water from entering the environment. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations. 		

SECTION 6: Accidental release m	easures
6.1. Personal precautions, protective	equipment and emergency procedures
General measures	: Spill area may be slippery. Prevent soil and water pollution. Prevent entry to sewers and public waters.
6.1.1. For non-emergency personnel	
Protective equipment	: When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required. Use protective clothing.
Emergency procedures	: Consider evacuation.
6.1.2. For emergency responders	
Protective equipment	: When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.
Emergency procedures	: No specific measures are necessary.
6.2. Environmental precautions	

Dike for recovery or absorb with appropriate material. Notify authorities if product enters sewers or public waters. Prevent soil and water pollution. Prevent liquid from entering sewers, watercourses, underground or low areas. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

For containment	: Large quantities: Contain large spillage with sand or earth.
Methods for cleaning up	: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Take up large spills with pump or vacuum and finish with dry chemical absorbent
Other information	: Use suitable disposal containers. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations. On water, recover/skim from surface and pour out in disposal container.

6.4. Reference to other sections

For further information refer to section 13.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 7: Handling and storage		
7.1. Precautions for safe handling		
Additional hazards when processed	: Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.	
Precautions for safe handling	: Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or smoke during use. Remove contaminated clothing and shoes.	
Hygiene measures	: Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse.	
7.2. Conditions for safe storage, including any incompatibilities		
Technical measures Storage conditions Incompatible products Maximum storage period	 Keep container tightly closed and in well ventilated place. Keep only in original container. Reacts vigorously with strong oxidizers and acids. 5 year 	

: 5 year

- : ≤ 40 °C
- : Keep away from : oxidizing materials. Strong acids.
- : Store at ambient temperature.
 - : Keep container tightly closed and dry.

7.3. Specific end use(s)

Special rules on packaging

Storage temperature Information on mixed storage

Storage area

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure-value for oil mist

: 10 mg/m3 (15 min.) or 5 mg/m3 (8 hours).

8.2. Exposure controls

Appropriate engineering controls:

Large quantities: Contain large spillage with sand or earth.

Personal protective equipment:

Gloves. In case of splash hazard: safety glasses. Eye protection should only be necessary where liquid could be splashed or sprayed.

Materials for protective clothing:	
PVC gloves. Neoprene or nitrile rubber gloves	
Hand protection:	

In case of repeated or prolonged contact wear gloves. The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream). The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

Eye protection:

Eye protection should only be necessary where liquid could be splashed or sprayed

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use. Avoid repeated or prolonged skin contact. If repeated skin contact or contamination of clothing is likely, protective clothing should be worn. Equipment should conform to EN 166.

Respiratory protection:

Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure. Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment. Respiratory protective equipment must be checked to ensure it fits correctly each time it is worn. Provided an air-filtering/air-purifying respirator is suitable, a filter for particulates can be used for mist or fume. Use filter type P or comparable standard. A combination filter for particles and organic gases and vapours (boiling point >65°C) may be required if vapour or abnormal odour is also present due to high product temperature. Use filter type AP or comparable standard.

Personal protective equipment symbol(s):



Environmental exposure controls: See Heading 12. See Heading 6.

Consumer exposure controls:

PVC gloves. Neoprene or nitrile rubber gloves.

Other information:

Do not put the product-soaked rags into the pockets of working clothes. Do not use cloths stained with the product to dry hands. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke during use. Wash contaminated clothing before reuse.

9.1. Information on basic physical and chemical properties

Physical state	: liquid
Appearance	: Oily. liquid.
Colour	: brown.
Odour	: characteristic.
Odour threshold	: No data available
рН	: No data available
Relative evaporation rate (butylacetate=1)	: < 0,1
Melting point	: No data available
Freezing point	: -30 °C
Boiling point	: > 280 °C
Flash point	: 200 °C
Auto-ignition temperature	: > 240 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour Pressure 20°C	: < 0,1 hPa
Relative vapour density at 20 °C	: > 1 (air=1)
Relative density	: No data available
Density	: 0,84 – 0,85 kg/l
Solubility	: insoluble in water.
Log Pow	: > 3
Viscosity, kinematic	: 50 – 100 mm²/s
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 0,6 – 7 vol %
9.2. Other information	

: 0%

: Gas/vapour heavier than air at 20'C.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 10: Stability and reactivity	
10.1. Reactivity	
Stable under normal conditions of use.	
10.2. Chemical stability	
Stable under normal conditions.	
10.3. Possibility of hazardous reactions	
Refer to section 10.1 on Reactivity.	
10.4. Conditions to avoid	
Moisture. Overheating.	
10.5. Incompatible materials	
Strong oxidizing agents. Strong acids.	
10.6. Hazardous decomposition products	
CO, CO2, POx, NOx, SOx, H2S. Metallic oxides.	

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	:	Not classified
Acute toxicity (dermal)	:	Not classified
Acute toxicity (inhalation)	:	Not classified

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 5000 mg/kg
LC50 Inhalation - Rat	> 5,53 mg/l

White mineral oil (petroleum) (8042-47-5)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal	> 2000 mg/kg Lapin
LC50 Inhalation - Rat (Dust/Mist)	> 5000 mg/l/4h

Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr)esters, zinc salts (84605-29-8)	
LD50 oral	3150 mg/kg (OECD 401 method)
LD50 dermal rat	> 2002 ml/kg
LC50 Inhalation - Rat	> 2,3 mg/l/4h
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
ENEOS GP4T Performance Racing 5W-30	
Viscosity, kinematic	50 – 100 mm²/s
Other information	: Toxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the toxicology of similar products. Likely route of exposure: ingestion, skin and eye.

SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general	 Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products.
Ecology - water Hazardous to the aquatic environment, short-term (acute)	This product floats on water and may affect the oxygen-balance in the water.Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

LC50 fish 1	100 mg/l
EC50 Daphnia 1	10000 mg/l

White mineral oil (petroleum) (8042-47-5)	
LC50 fish 1	> 100 mg/l Pimephales promelas
EC50 Daphnia 1	> 10000 mg/l EC50 48h - Daphnia magna [mg/l]
EC50 72h algae (1)	> 100 mg/l Scenedesmus quadricauda

Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr)esters, zinc salts (84605-29-8)	
LC50 fish 1	4,5 mg/l Oncorhynchus mykiss (Rainbow trout)
LC50 fish 2	46 mg/l Cyprinodon variegatus
EC50 Daphnia 1	23 mg/l EC50 48h - Daphnia magna [mg/l]
EC50 72h algae (1)	21 mg/l
ErC50 (algae)	21 mg/l 72h; Desmodesmus subspicatus
NOEC (acute)	1,8 mg/l
NOEC (chronic)	0,4 mg/l Daphnia magna
NOEC chronic crustacea	> 0,8 mg/l

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.2. Persistence and degradability	
ENEOS GP4T Performance Racing 5W-30	
Persistence and degradability	Not readily biodegradable.
obtained by treating a petroleum fraction with carbon numbers predominantly in the range	araffinic; Baseoil— unspecified; [A complex combination of hydrocarbons n hydrogen in the presence of a catalyst. It consists of hydrocarbons having of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F proportion of saturated hydrocarbons.] (64742-54-7)
Biodegradation	31 %
	imethylbutyl and iso-Pr)esters, zinc salts (84605-29-8)
Biodegradation	1,5 % (OECD 301B method)
12.3. Bioaccumulative potential	
ENEOS GP4T Performance Racing 5W-30	
Log Pow	> 3
Bioaccumulative potential	This product is not expected to bioaccumulate through food chains in the environment.
	imethylbutyl and iso-Pr)esters, zinc salts (84605-29-8)
Log Pow	0,56 Based on the n-octanol/water partition coefficient accumulation in organisms is not expected
Log Kow	0,56 Partition coefficient n-octanol/water [log Kow]
12.4. Mobility in soil	
ENEOS GP4T Performance Racing 5W-30	
Ecology - soil	Not miscible with water. Spillages may penetrate the soil causing ground water contamination. This product floats on water and may affect the oxygen-balance in the water.
12.5. Results of PBT and vPvB assessment	
No additional information available	
12.6. Other adverse effects	
No additional information available	
SECTION 13: Disposal considerations	
13.1. Waste treatment methods	
Regional legislation (waste) : Waste disposal recommendations :	Disposal must be done according to official regulations. Dispose in a safe manner in accordance with local/national regulations. Do not discharge into drains or the environment.
Additional information : Ecology - waste materials :	Hazardous waste. Every mixture with foreign substances such as solvents, brake- and cooling liquids is forbidden. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. When not empty dispose of this container at hazardous or special waste collection point.
European List of Waste (LoW) code :	13 02 06* - Synthetic engine, gear and lubricating oils

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 14: Transport information In accordance with ADR / RID / IMDG / IATA / ADN IMDG ΙΑΤΑ ADN RID ADR 14.1. UN number Not applicable Not applicable Not applicable Not applicable Not applicable 14.2. UN proper shipping name Not applicable Not applicable Not applicable Not applicable Not applicable 14.3. Transport hazard class(es) Not applicable Not applicable Not applicable Not applicable Not applicable 14.4. Packing group Not applicable Not applicable Not applicable Not applicable Not applicable 14.5. Environmental hazards Not applicable Not applicable Not applicable Not applicable Not applicable No supplementary information available

14.6. Special precautions for user

Overland transport Not applicable Transport by sea Not applicable Air transport Not applicable Inland waterway transport Not applicable Rail transport Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content

: 0 %

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 16: Other information Full text of H- and EUH-statements: Aquatic Chronic 2 Hazardous to the aquatic environment - Chronic Hazard, Category 2 Asp. Tox. 1 Aspiration hazard, Category 1 Eye Dam. 1 Serious eye damage/eye irritation, Category 1 Eye Irrit. 2 Serious eye damage/eye irritation, Category 2 Skin Irrit. 2 Skin corrosion/irritation, Category 2 H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.