

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Issue date: 30-1-2014 Revision date: 13-10-2020 Supersedes: 14-2-2020 Version: 2.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form	
Product name	
Product code	
Product group	

: Mixture : ENEOS Grand-LA 10W-40 : V161500428 : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Intended for general public Main use category Use of the substance/mixture Function or use category

: industrial use, professional use, consumer use

: Lubricant

: Lubricants and additives

#### 1.2.2. Uses advised against

No additional information available

### **1.3. Details of the supplier of the safety data sheet**

ENEOS Europe Limited 2F Bury House, 31 Bury Street, London, EC3A 5AR United Kingdom

### **1.4. Emergency telephone number**

Emergency number

: 0044 20 7186 0400 (Monday to Friday: 8:00 - 17:00)

# **SECTION 2: Hazards identification**

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

### 2.2. Label elements

Labelling according to Regulation (EC) No.	1272/2008 [CLP]
Precautionary statements (CLP)	: P102 - Keep out of reach of children.
EUH-statements	<ul> <li>EUH208 - Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs, calcium salts, Benzenesulfonic acid,methyl-mono-20-26-branched alkylderivates, calcium salts. May produce an allergic reaction.</li> <li>EUH210 - Safety data sheet available on request.</li> </ul>
Child-resistant fastening Tactile warning	: Not applicable : Not applicable

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2.3. Other hazards	
Other hazards not contributing to the classification	: This product floats on water and may affect the oxygen-balance in the water. The base oil contains less than 3% DMSO-extract measured according IP 346, therefore it is NOT classified as T/R45: May cause cancer" (Note L).". USED ENGINE OILS: Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.

# SECTION 3: Composition/information on ingredients

# 3.1. Substances

### Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Lubricating oils (petroleum), C20-C50, hydrotreated neutral oil-based	(CAS-No.) 72623-87-1 (EC-No.) 276-738-4 (REACH-no) 01-2119474889-13	35 – 50	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.]	(CAS-No.) 64742-54-7 (EC-No.) 265-157-1 (EC Index-No.) 649-467-00-8 (REACH-no) 01-2119484627-25	25 – 35	Asp. Tox. 1, H304
Highly refined mineral oil (C15 -C50) substance with a Community workplace exposure limit	(REACH-no) 01-2119471299-27, 01- 2119484627-25, 01-2119487077-29	10 – 25	Not classified
Derivative of amines, polyethylene poly-compunds with (polybutenyl) succinic anhydride, borates	(CAS-No.) 134758-95-5 (EC-No.) 603-861-6	3 – 5	Aquatic Chronic 4, H413
Amines, polyethylenepoly-,reaction products with 1,3- dioxolan-2-2one and succinic anhydride monopolyisobutenyl derivs	(CAS-No.) 147880-09-9 (EC-No.) 604-611-9	1 – 3	Aquatic Chronic 4, H413
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	(CAS-No.) 68784-31-6 (EC-No.) 272-238-5 (REACH-no) 01-2119657973-23	1 – 3	Eye Dam. 1, H318 Aquatic Chronic 2, H411
Bis(nonylfenyl)amine	(CAS-No.) 36878-20-3 (EC-No.) 253-249-4 (REACH-no) 01-2119488911-28	1 – 3	Aquatic Chronic 4, H413
Benzenesulfonic acid,methyl-mono-20-26-branched alkylderivates, calcium salts	(CAS-No.) 722503-69-7	1 – 3	Skin Sens. 1B, H317 Aquatic Chronic 4, H413

Full text of H-statements: see section 16

4.1. Description of first aid measures	
First-aid measures general       : Seek medical attention if ill effect develops.         First-aid measures after inhalation       : Take victim to fresh air, in a quiet place, in an half laying position and if ne medical advice. Allow the victim to rest.	ecessary take

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

First-aid measures after skin contact First-aid measures after eye contact First-aid measures after ingestion	<ul> <li>Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. High-pressure injection under skin may cause serious damage. Seek medical attention if ill effect or irritation develops.</li> <li>Remove contact lenses, if present and easy to do. Continue rinsing. Ensure adequate flushing of eyes by separating eyelids with the fingers. Obtain medical attention if pain, blinking, tears or redness persist.</li> <li>Consult a doctor/medical service if you feel unwell. If vomiting occurs spontaneously, keep head below the hips to prevent aspiration. Do not induce vomiting.</li> </ul>
4.2. Most important symptoms and effects,	both acute and delayed
Symptoms/effects after inhalation	: At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.
Symptoms/effects after skin contact	: Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis. High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.
Symptoms/effects after eye contact	: Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.
Symptoms/effects after ingestion	: Bad taste. Unlikely to cause harm if accidentally swallowed in small doses, though larger quantities may cause nausea and diarrhoea.
Symptoms/effects upon intravenous administration	: Unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures		
5.1. Extinguishing media		
Suitable extinguishing media Unsuitable extinguishing media	<ul> <li>carbon dioxide (CO2), dry chemical powder, foam. Water fog.</li> <li>Do not use a heavy water stream. Use of heavy stream of water may spread fire.</li> </ul>	
5.2. Special hazards arising from the substance or mixture		
Fire hazard Explosion hazard	<ul> <li>Combustion generates: CO, CO2, POx, NOx, SOx, H2S. Metallic oxides.</li> <li>Not expected to be a fire/explosion hazard under normal conditions of use.</li> </ul>	
5.3. Advice for firefighters		
Precautionary measures fire Firefighting instructions Protection during firefighting Other information	<ul> <li>Do not enter fire area without proper protective equipment, including respiratory protection.</li> <li>Use water spray or fog for cooling exposed containers.</li> <li>Use self-contained breathing apparatus and chemically protective clothing.</li> <li>Prevent fire fighting water from entering the environment. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations.</li> </ul>	

SECTION 6: Accidental release measures		
6.1. Personal precautions, protective equipment and emergency procedures		
General measures	: Spill area may be slippery. Prevent soil and water pollution. Prevent entry to sewers and public waters.	
6.1.1. For non-emergency personnel		
Protective equipment	: When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required. Use protective clothing.	
Emergency procedures	: Consider evacuation.	
6.1.2. For emergency responders		
Protective equipment	: When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.	
Emergency procedures	: No specific measures are necessary.	

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 6.2. Environmental precautions

Dike for recovery or absorb with appropriate material. Notify authorities if product enters sewers or public waters. Prevent soil and water pollution. Prevent liquid from entering sewers, watercourses, underground or low areas. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

6.3. Methods and material for containment and cleaning up		
For containment	: Large quantities: Contain large spillage with sand or earth.	
Methods for cleaning up	: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Take up large spills with pump or vacuum and finish with dry chemical absorbent.	
Other information	: Use suitable disposal containers. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations. On water, recover/skim from surface and pour out in disposal container.	

# 6.4. Reference to other sections

#### For further information refer to section 13.

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Additional hazards when processed	: Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.
Precautions for safe handling	: Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or smoke during use. Remove contaminated clothing and shoes.
Hygiene measures	: Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse.
7.2. Conditions for safe storage, including a	any incompatibilities
Technical measures	: Keep container tightly closed and in well ventilated place.

Technical measures	: Keep container tightly closed and in well ventilated place.
Storage conditions	: Keep only in original container.
Incompatible products	: Reacts vigorously with strong oxidizers and acids.
Maximum storage period	: 5 year
Storage temperature	: ≤ 40 °C
Information on mixed storage	: Keep away from : oxidizing materials. Strong acids.
Storage area	: Store at ambient temperature.
Special rules on packaging	: Keep container tightly closed and dry.

## 7.3. Specific end use(s)

No additional information available

8.1. Control parameters		
Highly refined mineral oil (C15	-C50)	
EU - Occupational Exposure Limits		
IOELV TWA (mg/m <sup>3</sup> )	5 mg/m³	

13-10-2020 (Version: 2.0)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

#### 8.2. Exposure controls

#### Appropriate engineering controls:

Large quantities: Contain large spillage with sand or earth.

### Personal protective equipment:

Gloves. In case of splash hazard: safety glasses. Eye protection should only be necessary where liquid could be splashed or sprayed.

#### Materials for protective clothing:

PVC gloves. Neoprene or nitrile rubber gloves

#### Hand protection:

In case of repeated or prolonged contact wear gloves. The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream). The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

#### Eye protection:

Eye protection should only be necessary where liquid could be splashed or sprayed

#### Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use. Avoid repeated or prolonged skin contact. If repeated skin contact or contamination of clothing is likely, protective clothing should be worn. Equipment should conform to EN 166.

#### **Respiratory protection:**

Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure. Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment. Respiratory protective equipment must be checked to ensure it fits correctly each time it is worn. Provided an air-filtering/air-purifying respirator is suitable, a filter for particulates can be used for mist or fume. Use filter type P or comparable standard. A combination filter for particles and organic gases and vapours (boiling point >65°C) may be required if vapour or abnormal odour is also present due to high product temperature. Use filter type AP or comparable standard.

#### Personal protective equipment symbol(s):



#### Environmental exposure controls:

See Heading 12. See Heading 6.

#### Consumer exposure controls:

PVC gloves. Neoprene or nitrile rubber gloves.

#### Other information:

Do not put the product-soaked rags into the pockets of working clothes. Do not use cloths stained with the product to dry hands. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke during use. Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties		
9.1. Information on basic physical and o	chemical properties	
Physical state	: liquid	
Appearance	: Oily. liquid.	
Colour	: brown.	
Odour	: characteristic.	
Odour threshold	: No data available	
pH	: No data available	
Relative evaporation rate (butylacetate=1)	: < 0,1	
13-10-2020 (Version: 2.0)	EN (English)	5/10

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Melting point Freezing point Boiling point Flash point Auto-ignition temperature Decomposition temperature Flammability (solid, gas) Vapour Pressure 20°C Relative vapour density at 20 °C Relative density Density Solubility Log Pow Viscosity, kinematic Viscosity, dynamic	$\begin{array}{l} \leq -42 \ ^{\circ}\text{C} \\ \text{No data available} \\ \begin{array}{l} > 280 \ ^{\circ}\text{C} \\ \begin{array}{l} 233 \ ^{\circ}\text{C} \\ \end{array} \\ \begin{array}{l} > 240 \ ^{\circ}\text{C} \\ \end{array} \\ \begin{array}{l} \text{No data available} \\ \end{array} \\ \begin{array}{l} \text{No data available} \\ \end{array} \\ \begin{array}{l} < 0,1 \ \text{hPa} \\ \end{array} \\ \begin{array}{l} > 1 \ (air=1) \\ \end{array} \\ \begin{array}{l} \text{No data available} \\ \end{array} \\ \begin{array}{l} 0,845 - 0,855 \ \text{kg/l} \\ \end{array} \\ \begin{array}{l} \text{insoluble in water.} \\ \end{array} \\ \begin{array}{l} > 3 \\ \end{array} \\ \begin{array}{l} 150 - 300 \ \text{mm}^2/\text{s} \\ \end{array} \\ \begin{array}{l} \text{No data available} \end{array} \end{array}$
Explosive properties Oxidising properties Explosive limits	<ul> <li>No data available</li> <li>No data available</li> <li>0,6 – 7 vol %</li> </ul>

### 9.2. Other information

VOC content Other properties : 0 %

: Gas/vapour heavier than air at 20'C.

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Stable under normal conditions of use.

**10.2. Chemical stability** 

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

10.4. Conditions to avoid

Moisture. Overheating.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids.

**10.6. Hazardous decomposition products** 

CO, CO2, POx, NOx, SOx, H2S. Metallic oxides.

# SECTION 11: Toxicological information

11.1. Information on toxicologica	al effects	
Acute toxicity (oral)	: Not classified	
Acute toxicity (dermal)	: Not classified	
Acute toxicity (inhalation)	: Not classified	

Bis(nonylfenyl)amine (36878-20-3)	
LD50 oral rat	> 5000 mg/kg (OECD 401 method)
LD50 dermal rat	> 2000 ml/kg (OECD 402 method)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 5000 mg/kg
LC50 Inhalation - Rat	> 5,53 mg/l
	·
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: The mixture contains a substance with skin sensitization potential, but allergic skin reactions
	are not expected.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
ENEOS Grand-LA 10W-40	
Viscosity, kinematic	150 – 300 mm²/s

Other information	: Toxicological data have not been determined specifically for this product. Information given
	is based on a knowledge of the components and the toxicology of similar products. Likely
	route of exposure: ingestion, skin and eye.

SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general	<ul> <li>Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products.</li> </ul>
Ecology - water Hazardous to the aquatic environment, short-term (acute)	<ul><li>This product floats on water and may affect the oxygen-balance in the water.</li><li>Not classified</li></ul>
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Bis(nonylfenyl)amine (36878-20-3)	
LC50 fish 1	> 100 mg/l 96h; Brachydanio rerio (zebra-fish)
EC50 Daphnia 1	> 100 mg/l EC50 48h - Daphnia magna [mg/l]
EC50 72h algae (1)	600 mg/l
ErC50 (algae)	> 100 mg/l 72h; Desmodesmus subspicauts

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)	
LC50 fish 1	100 mg/l
EC50 Daphnia 1	10000 mg/l

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.2. Persistence and degradability	
ENEOS Grand-LA 10W-40	
Persistence and degradability	Not readily biodegradable.
Phosphorodithioic acid, mixed 0,0-bis(sec-	Bu and 1,3-dimethylbutyl) esters, zinc salts (68784-31-6)
Biodegradation	< 5 %
Bis(nonylfenyl)amine (36878-20-3)	
Biodegradation	0 % Sturm - 28 days
obtained by treating a petroleum fraction wit carbon numbers predominantly in the range	paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons th hydrogen in the presence of a catalyst. It consists of hydrocarbons having of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F proportion of saturated hydrocarbons.] (64742-54-7)
Biodegradation	31 %
12.3. Bioaccumulative potential	
ENEOS Grand-LA 10W-40	> 3
Bioaccumulative potential	This product is not expected to bioaccumulate through food chains in the environment.
Phosphorodithioic acid, mixed O,O-bis(sec-	Bu and 1,3-dimethylbutyl) esters, zinc salts (68784-31-6)
Log Pow	≤ 4,5
Bis(nonylfenyl)amine (36878-20-3)	
Bioconcentration factor (BCF REACH)	1584,89
12.4. Mobility in soil	
ENEOS Grand-LA 10W-40	
Ecology - soil	Not miscible with water. Spillages may penetrate the soil causing ground water contamination. This product floats on water and may affect the oxygen-balance in the water.
12.5. Results of PBT and vPvB assessment	
No additional information available	
12.6. Other adverse effects	
No additional information available	
SECTION 13: Disposal considerations	
13.1. Waste treatment methods	
Regional legislation (waste) :	Disposal must be done according to official regulations.

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Do not discharge
	into drains or the environment.
Additional information	: Hazardous waste.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ecology - waste materials	Every mixture with foreign substances such as solvents, brake- and cooling liquids is forbidden. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. When not empty dispose of this container at hazardous or special waste collection point.
European List of Waste (LoW) code	13 02 06* - Synthetic engine, gear and lubricating oils

# **SECTION 14: Transport information**

#### In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	ΙΑΤΑ	ADN	RID
14.1. UN number	-	· · · · ·		
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shippin	g name	· · · · ·		
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard o	class(es)	· · · ·		
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group		· · ·		
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental haz	zards			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

### 14.6. Special precautions for user

Overland transport Not applicable Transport by sea Not applicable Air transport Not applicable Inland waterway transport Not applicable Rail transport Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

# SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

: 0 %

VOC content

#### 15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

# SECTION 16: Other information

Full text of H- and EUH-statements:		
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2	
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4	
Asp. Tox. 1	Aspiration hazard, Category 1	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1	
Skin Sens. 1B	Skin sensitisation, category 1B	
H304	May be fatal if swallowed and enters airways.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H411	Toxic to aquatic life with long lasting effects.	
H413	May cause long lasting harmful effects to aquatic life.	
EUH208	Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs, calcium salts, Benzenesulfonic acid,methyl-mono-20-26-branched alkylderivates, calcium salts. May produce an allergic reaction.	
EUH210	Safety data sheet available on request.	

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.